

1 Fruitful functions

A **fruitful function** is a function that returns a value when it is called. Most of the builtin functions that we have used are fruitful. For example, the function `abs` *returns* a new number – namely, the absolute value of its argument:

```
>>> abs(-42)
42
```

Some functions are *not* fruitful. For example, suppose `franklin` refers to a Turtle object, the function call `franklin.forward(100)` does *not* return anything. Instead it causes `franklin` to move forward. In addition, *all* of the functions defined in Handout #11 are *not* fruitful.

2 Defining a fruitful function

If we want a function to return a result to the caller of the function, we use the **return** statement. For example, here we define two fruitful functions. The second one, `circle_area`, calls the first one, `square`, to square the radius.

```
import math

def square(x):
    return x * x

def circle_area(diameter):
    radius = diameter / 2.0
    return math.pi * square(radius)
```

In general, a return statement consists of the **return** keyword followed by an expression, which is evaluated and returned to the function caller.

How python evaluates a return statement Python evaluates fruitful functions pretty much the same way as non-fruitful ones (see Handout #11). The only thing new is how it executes a **return** statement. Here's how:

1. Evaluate the expression. This produces a memory address.
2. Pass back that memory address to the caller. Leave the function *immediately* and return to the location where the function was called.

Python returns immediately when it reaches a **return** statement. The **print** statement in the function body below will *never* be executed:

```
def square(x):
    return x * x                # python leaves function here...
    print "I am NEVER printed!" # ... and never gets to here.
```

3 Return vs. print, which one to use?

Many beginning programmers get confused about the difference between **return** and **print**. The **return** statement sends a data value back to the caller of the function; the **print** statement displays a data value on the screen. You will need to use *both*. But when to use which? Here's a general rule of thumb: *Use return to share the result with another part of your program; use print to share the result with the user.*

The `square` function *must* use a **return** statement because it is called inside the `circle_area` function. In other words, the point of this function is to share the result (i.e., the squared number) with another part of our program (i.e., the `circle_area` function).

4 NoneType error

In python, *every* function is fruitful even if the body does not contain a **return** statement. In this case, the function will return a special value called `None`, which has type `NoneType`.

Example: suppose we change the **return** in `square` to **print**. Here's what happens when we call `circle_area` passing in 4 as its argument.

```
>>> circle_area(8)
16.0
Traceback (most recent call last):
  File "<stdin>", line 1, in <module>
  File "fruitful_functions.py", line 8, in circle_area
    return math.pi * square(radius)
TypeError: unsupported operand type(s) for *: 'float' and 'NoneType'
```

We get an error about a `NoneType` because `circle_area` is trying to multiply `math.pi` with the return value of `square`, which is `None`, and so it crashes. Also notice that just before the error, the program *prints* the number 16.0 (which is $(8/2)^2$).

5 Exercises

1. Write a function that computes the area of a ring with a given diameter and thickness.
2. Write a function, `max_of_two`, that takes two numbers and returns the larger number.
3. Write a function, `max_of_three`, that takes three numbers and returns the largest number.